



CONCRETE OF PG 140/100  
AND U. 100.1, 100.2 TO BE COVERED WITH 100MM POLYETHYLENE  
DURING CONSTRUCTION TO PREVENT WATER PENETRATION.

ARCHITECT

DESIGNED BY	DATE
... ..	...
... ..	...
... ..	...
... ..	...

... ..  
... ..  
... ..  
... ..

...	...	...	...	...
...	...	...	...	...
...	...	...	...	...
...	...	...	...	...
...	...	...	...	...
...	...	...	...	...
...	...	...	...	...
...	...	...	...	...

... ..  
... ..  
... ..

302/430/1/...  
... ..

- The sanction is valid for 3 years from date of sanctioning
- Information required by the applicant to this and attached herewith shall be furnished to the applicant.
- All building materials used in the construction shall conform to standards specified in the S.P.C. of India.
- Necessary steps should be taken to satisfy the safety of lives of the adjoining public and private property during construction.
- Design of all structural members including that of the foundation should conform to standards specified in the S.P.C. of India.

The recommended load areas shall not be used for any permanent or temporary construction of erections or designed open air parking spaces or any other erections. Violation of the same will automatically void the sanction / completion certificate.

1. There should not be any crane or any other heavy machinery used on the site.  
2. South 24 Parganas Zilla Parishad will not be liable if any damage arises at the site.- The construction should be carried out per sanctioned plan and sanctioned plans under the supervision of qualified employed engineers.
- Construction of garbage pit, soak pit & waste water should be done by the owners.
- Any deviation of the sanctioned plan shall mean demolition.