

REVISED SANCTIONED PLAN

File No. 594/124/REV/KMDA

- Voted and recommended for sanction the building plan No. 594/124/REV/KMDA. Height... 9.1 mt. Subject to the condition
- Before starting any construction the site must conform with the plans Sanctioned and all the condition as proposed in the plan should be fulfilled.
- All building materials necessary for construction should conform to standard specified in the N.B.C. of India
- Necessary steps should be taken for safety of lives of the adjoining public and private property during construction.
- Construction site should be maintained to prevent mosquito breeding.
- Design of all Structural members including that of the foundation should conform to standard specified in the N.B.C. of India
- The sanction is valid for 3 years from date of sanctioning
- Information required by the applicant to this end are:-
Commencement of work.
Completion of structural work up to plinth.
Completion of work.
- No rain water pipe should be fixed or discharged on Road or Footpath.
- The construction should be carried out as per specification of I.S. Code and sanctioned plan under the supervision of qualified empanelled engineers.
- Construction of garbage vat, soak pit & waste water should be done by the owners.
- Any deviation of the sanctioned plan shall mean demolition

The non-converted land areas shall not be used for any permanent or temporary constructions / erections / designated open car parking spaces or any other structures. Violation of the same will automatically revoke the sanction / completion certificate.

1. There should not be any corner in respect of the complains from any plan.
2. "South 24 Parganas Zilla Parishad" will not be liable if any dispute arises at the site

ASSISTANT ENGINEER
South 24 Pgs. Z.P.

DISTRICT ENGINEER
South 24 Pgs. Z.P.

SCHEDULE OF TYPICAL BEAMS (SIZE & REINFORCEMENT)

BEAM NO.	BEAM TYPE	SPAN (m)	DEPTH (m)	REINFORCEMENT
1	1ST FLOOR	3.0	0.3	10mm @ 150mm
2	2ND FLOOR	3.0	0.3	10mm @ 150mm
3	3RD FLOOR	3.0	0.3	10mm @ 150mm
4	4TH FLOOR	3.0	0.3	10mm @ 150mm
5	5TH FLOOR	3.0	0.3	10mm @ 150mm
6	6TH FLOOR	3.0	0.3	10mm @ 150mm
7	7TH FLOOR	3.0	0.3	10mm @ 150mm
8	8TH FLOOR	3.0	0.3	10mm @ 150mm
9	9TH FLOOR	3.0	0.3	10mm @ 150mm
10	10TH FLOOR	3.0	0.3	10mm @ 150mm

SCHEDULE OF TYPICAL TIE BEAMS (SIZE & REINFORCEMENT)

BEAM NO.	BEAM TYPE	SPAN (m)	DEPTH (m)	REINFORCEMENT
1	1ST FLOOR	3.0	0.3	10mm @ 150mm
2	2ND FLOOR	3.0	0.3	10mm @ 150mm
3	3RD FLOOR	3.0	0.3	10mm @ 150mm
4	4TH FLOOR	3.0	0.3	10mm @ 150mm
5	5TH FLOOR	3.0	0.3	10mm @ 150mm
6	6TH FLOOR	3.0	0.3	10mm @ 150mm
7	7TH FLOOR	3.0	0.3	10mm @ 150mm
8	8TH FLOOR	3.0	0.3	10mm @ 150mm
9	9TH FLOOR	3.0	0.3	10mm @ 150mm
10	10TH FLOOR	3.0	0.3	10mm @ 150mm

SCHEDULE OF SLAB REINFORCEMENT

SLAB NO.	SLAB TYPE	SPAN (m)	DEPTH (m)	REINFORCEMENT
1	1ST FLOOR	3.0	0.3	10mm @ 150mm
2	2ND FLOOR	3.0	0.3	10mm @ 150mm
3	3RD FLOOR	3.0	0.3	10mm @ 150mm
4	4TH FLOOR	3.0	0.3	10mm @ 150mm
5	5TH FLOOR	3.0	0.3	10mm @ 150mm
6	6TH FLOOR	3.0	0.3	10mm @ 150mm
7	7TH FLOOR	3.0	0.3	10mm @ 150mm
8	8TH FLOOR	3.0	0.3	10mm @ 150mm
9	9TH FLOOR	3.0	0.3	10mm @ 150mm
10	10TH FLOOR	3.0	0.3	10mm @ 150mm

