STATE LEVEL ENVIRONMENT IMPACT ASSESSMENT AUTHORITY

oura Bhavan, Block 'FD'-415A, 4th Floor, Sector – III,

Salt Lake, Kolkata – 700 106 Telefax No. 033 2337 0268

Website: www.environmentwb.gov.in

Date: 05 / 07 /2016

No. 1471 / EN/T-II-1/074/2014

Kolkata - 700 016 Room No. #5B, 5th Floor 99A, Park Street, Siddha Park M/s. Arch Infra Properties Pvt. Ltd

Sir,

SUB. Gopalpur Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal. 139,140,143,144,534, Mouza -Environmental Clearance Teghoria & proposed residential Complex at RS dag no. & Atghara, JLNo. 9 & 10, PS – Rajarhat, Rajarhat-

Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal. 139,140,143,144,534, Mouza - Teghoria & Atghara, JL No. 9 & 10, PS - Rajarhat, Rajarhat-Gopalpur communications for environmental clearance for the proposed residential Complex at RS dag no. has reference Ö your application submitted on 10/09/2014 and subsequent

B+G+10 & 1 block of B+G+7 storied having 297 nos. residential flats. The proposed project proposal is for construction of a Residential Complex comprising of 7 Blocks of The proposal has been examined and processed in accordance with the EIA Notification, 2006

considered are given below: It is noted that the salient features of the project for which Environmental clearance has been

: 3882.51 sqm. (24.77% of land area)	Total Paved Area
: 2782.92 sqm. (17.77% of land area)	Other green Area
: 3452.73 sqm. (22.03% of land area)	Exclusive tree plantation area
: 5553.11 sqm. (35.43% of land area)	Ground Coverage
: 61185.046 sqm.	Total Built-up Area
: 0.85 TPD (to be disposed off through in-house compost plant & Municipal Waste disposal system)	Solid waste disposal
: 52KLD (to be discharged to municipal drainage)	Treated wastewater discharged
: 112 KLD (toilet flushing, landscaping, road washing etc.)	Treated Wastewater recycled
: 182 KLD (to be treated in STP)	Wastewater generated
: 151 KLD (Rajarhat-Gopalpur municipality supply)	Fresh Water requirement
: 271 KLD (Operation stage)	Total Water requirement
: 22°37'18.47"N.& 88°26'29.78"E	Latitude & Longitude
: 1669 (1485 - residents, 150 - floating, 20 - service, club-14)	Expected Population
: 15671.272 sqm	Land Area



dag no. 139,140,143,144,534, Mouza - Teghoria & Aighe Municipality Ward No. 9, Dist — Conditions for environmental clearance for 24 Parganas (Nonth) omplex by Mis Arch Infra Properties Pvt. Ltd. at RS & 10, PS – Rajarhat, Rajarhat-Gopalpur

:DG Sets (4x250 KVA)	Backup Power
addition to stand alone solar street lights.	
: At least 30 KW of solar power to be generated and utilized in	Use of solar power
: J.4 MW; WBSEDCL	Power requirement
Irom solar power.	
: 24 nos. & atteast 30 KW of total power requirement shall be met	No. of solar street light
:: proposed-21 & existing-6 nos:	No. of Trees to be planted
: 396.nos (basement – 228, ground – 123, open-45)	No. of Parking Spaces proposed

also perused recommendations of the State Level Expert Appraisal Committee (SEAC). After due consideration of the project proposal, and the recommendations of the State Level Expert Appraisal 2006 of Ministry of Environment & Forests, GOI subject to strict compliance of terms and conditions Clearance to the project as per provisions of the EIA notification no. S.O. 1533 Committee (SEAC), the State Level Environment Impact Assessment Authority accords Environmental State Level Environment Impact Assessment Authority (SEIAA), examined the proposal and (E) dt. 14th September,

Part A - SPECIFIC CONDITIONS

Ц 6

1. Construction Phase

Facility of labourers during construction: -

- Provision of drinking water, wastewater disposal and solid waste management should be ensured for labour camps. Water usage during construction should be optimized to avoid any wastage.
- sanitation. Sewage generated from the areas occupied by the construction labourers have to be directed into the existing sewage drain of the area. In case of non availability of the sewer system, an onsite treatment system has to be provided. Proper sanitation facilities should be provided for construction workers to ensure environmental
- The scaffolds, stairs and platforms for construction works and the workers must be secured as far as
- Ţ, Health and safety of the workers should be ensured during construction. Personnel protective equipment like shoes, helmets, earnuffs, earplugs etc. should be provided to the workers. For vibration control damped tools must be used and the number of hours that a worker uses them must such protection, if any. The Management must ensure that the workers put them while doing work that needs
- be provided with proper toilet facilities. Rest and convenience shelter for workers with creche facility, if required, particularly women, must

Steps to avoid disturbance during construction:-

- sediment control measures to be adopted before ensuing construction activities. walls for use in horticulture / landscape development within the project site. Adequate erosion and All the topsoil excavated during construction activities should be under cover/stored by retaining
- Ξ: Prior permission should be obtained from the competent authority for demolition of the existing recycling and disposal method to be followed. and construction activity. The plans should identify wastes to be generated and designate handling structure, if any, Waste recycling plans should be developed for prior to beginning of demolition



Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal. dag no. 139,140,143;144,534, Mouza — Teghoria & Atgliara, JL No. 9 & 10, PS — Rajarhat, Rajarhat-Gopalpui Conditions for environmental clearance for the Residential Complex by M/s. Arch Infra Properties Pvt. Ltd. at RS

- Disposal of muck including excavated material during construction phase should not create any for general safety and health aspects adverse effects on the neighbouring communities and disposed off taking the necessary precautions
- 7 conform to E(P) Rules prescribed for all and noise emission standards. Diesel generator sets during construction phase should have acoustic enclosures and should
- :< peaking hours conform to applicable air and noise emission standards and should be operated only during non-Vehicles / equipment deployed during construction phase should be in good condition and should
- ≰. should be ensured during construction phase. Fortnightly monitoring of ambient air quality (SPM, SO2 and NOx) and equivalent noise levels Ambient noise levels should conform to residential standards both during day and night
- <u>⊀</u>: Construction spoils including bituminous material and other hazardous materials including oil from trap should be installed where there is deployment of heavy machineries. such material must be secured so that they should not leach into the ground water. If necessary, oil construction equipments must not be allowed to contaminate watercourses and the dumpsites for
- ¥:: Regular supervision of the above and other measures should be in place all through the construction proposed project activity should be minimized as far as practicable. phase so as to avoid disturbance to the surroundings. Discomfort in the neighbourhood due to the
- × carried out for a limited period during nighttime. activities including Piling work, Operation of Ready Mix Plant and Vibrator etc. should not be carried out during the night time (10 P.M. to 6 A.M.). Only essential operations, if any, may be Loading and unloading operations should not be carried out in open areas and should be preferably done during day time, if there is any major settlement in the surrounding areas. The construction
- × major settlement in the surrounding areas. The proponent must ensure that no driven piles shall be proposed for this project, if there is any
- <u>×</u>. material storages adequately covered and contained so that they are not exposed to winds 15m-screen and adequate sprinkler agrangement shall be provided. Care should be taken to keep all
- xii. Use of Ready-Mix concrete is recommended for this project.
- xiii. Adequate measures to be adopted to avoid wastage of water for curing of concrete structures
- xiv. Adequate mitigative measures should be adopted to control dust emissions, noise and vibrations Vehicles should conform to Pollution under control (PUC) norms. from construction activities. Vehicles and construction machineries should be properly maintained
- xv. Locally available materials with less transportation cost should be used preferably
- xvi. Promotion of use of cleaner fuel and fuel quality improvement should be done. Excessive energy consumption and fuel usage should be avoided.
- xvii. Accumulation / stagnation of water should be avoided to ensure vector control

Selection of materials for better energy efficiency:-

- Use of energy efficient construction materials should be ensured to achieve the desired thermal =
- design for daylight integration should be considered. Design layout should ensure adequate solar access and ventilation. Proper planning and window
- Ξ Fly Ash is to be used for construction as per Notification No. the Ministry of Environment & Forests, Govt, of India. amended vide Notification No. S.O. 979(E) dated 27.8.2003 and S.O. 2804(E) dated 03.11.2009 of S.O. 763(E) dated 14.09,1999
- Y. Construction should conform to the requirements of local seismic regulations. The project proponent should obtain permission for the plans and designs including structural design, standard and specifications from concerned authority.

001

dag no. 139,140,143,144,534, Mouza – Teghoria & Atghara, JL No. 9 & 10, PS – Rajarhat, Rajarhat-Gopalpur Municipality Ward No. 9, Dist - 24 Pargands (North), West Bengal. Conditions for environmental clearance for the Residential Complex by M/s. Arch Infra Properties Pvt. Ltd. at RS

- Materials with low embodied energy and high strength should be used preferably. Construction technologies that require less material and possess high strength should be adopted
- ≦. The building will be constructed and provisioned to use natural sunlight to the maximum during the
- vii. Use of alternate building materials and alternate construction techniques should be considered apart from the conventional materials and methods. Use of hollow unit masonry should be considered.
- viii. Use of energy efficient lighting systems e.g. High Pressure Sodium Vapour (HPSV) Lamps, LED etc. should be promoted. Solar energy should be used for butdoor lighting. Adequate no. of solar lights should be installed for external lighting as per norms. All common area lighting will be LED
- × Solar water heating arrangement will be done for water heating.
- ensuring natural ventilation and daylighting. Passive solar cooling to be incorporated in building design. Buildings should be oriented -157 --for
- Σ Proper insulation of roof should be provided to achieve desired thermal comfort. Use of light incorporated coloured, reflective roofs having an SRI (solar reflectance index) of 50% or more should be
- ž: should be incorporated. Use of high albedo or reflective pavements to keep parking lots, pavements and inside roads cool
- XIII. Guidelines to the occupants should include usage efficiency measures such as energy efficient lighting and water efficient system.
- xiv.Reduce hard paving-onsite (open area surrounding building premises) and/or provide shade on hard paved surfaces to minimize heat island effect and imperviousness of the site
- Adequate open space, greenery and water bodies to be provided as per rules.
- xvi. Any proposed building with air-conditioning facility should follow the norms proposed in the ECBC regulations framed by the Bureau of Energy Efficiency. Chillers should be CFC & HCFC free.
- xvii. Restrict the use of glazed surface as per National Building Code 2005

Water Body Conservation:-

bodies are to be kept in natural conditions without disturbing the ecological habitat. Water body, if any, should not be lined and their embankments should not be cemented. The water

Plantation Proposal:-

- The unit should strictly abide by The West Bengal Trees (Protection and Conservation in Non-Forest Areas) Rules, 2007. The proponent should undertake plantation of trees over atleast 20% of
- No tree can be felled without prior permission from the Tree Cutting Authority constituted as per subsequent rules. Bengal Trees (Protection and Conservation in Non-Forest Areas) Act, 2006 and
- The proponent should plant at least 240 no. trees of recommended species in addition to 6 nos. existing trees to be retained. Indicative list of species is given at Annexure canopy cover are planning should include plantation of native desirable. Water intensive and/or invasive species should not be used for species. The species with heavy foliage and wide I. The landscape

Water supply:-

Supply. Ground water should not be abstracted without permission of the competent authority as per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005. Water requirement during construction phase shall be met from Rajarhat-Gopalpur Municipality



Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal, dag no. 139,140,143,144,534, Mouza – Teghorid & Aighdra, JL No. 9 & 10, PS – Rajarhat, Rajarhat-Gopalpur Conditions for environmental clearance for the Residential Complex by M/s. Arch Infra Properties Pvt. Ltd. at RS

0) / \$ = 500 - 700 - 700 - 700 - 700

Sewage Treatment Plant:-

discharged to municipal facility. in toilet flushing, internal road and payement cleaning and landscaping and remaining part will be As per the proposal submitted by the proponent waste water shall be treated in STP and to be used

Storm water Management & Mitigation of Heat Island Effect.

- Imperviousness of the site shall not exceed the NBC (National Building Code 2005) standards for imperviousness factor applicable to different types of area.
- Total paved area of site under parking goads, paths or any other use should not exceed 25% of the
- Minimum 50% of paved area on site should have pervious paving or shaded under vegetation or topped with finish having solar reflectance of 0.5 or higher.
- shock load on the drainage system and impact on receiving water body. surrounding settlements. Storm water management plan should be implemented so as to prevent sudden discharge of excessive volumes of storm water to the receiving waters thus reducing the Adequate storm water drainage network to be designed for the project without disturbing the
- increasing on site infiltration and managing storm water run off. Disruption to the natural hydrology of the site should be minimised by reducing impervious cover,
- ≤. Heat island effect should be minimized by use of shading or reflective surfaces, mainly the surfaces roofs should be provided in the buildings. that contribute to the heat island effect lie. streets, sidewalks, parking lots and buildings. White

Rain Water Harvesting Scheme:-

- Committee (SEAC) available in the website (http://www.wbpcb.gov.in). The proponent must follow the Rainwater Harvesting Guidelines of the State Expert Appraisal
- =: The proponent must collect rainwater from roof-top carchinents and reuse for various purposes harvesting rainwater. after necessary cleaning. Adequate retention time and storage provisions should be provided for
- Storage capacity of harvested rain water should be at least 300 KL and remaining harvested rainwater to be recharged. . -.
- ₹ The proponent must ensure proper depth of recharge well for ground water recharging
- Adequate firefighting storage should be provided as per norms

Municipal Solid Waste Management :-

access shall be provided. Adequate provision shall be made for storage and segregation of solid waste and adequate means

Transport Management: -

- uninterrupted traffic movement in the area during construction as well as operation phase Both internal and external traffic planning and management should be adequate 5 ensure
- made at the entry & exit. Proper traffic management plan should be adopted in consultation with The design of service road and the entry and exit from the project area should conform to the norms & standards of competent authority for traffic management. Bell mouth type arrangement should be
- Ξ Clarified Wastewater will be used for sprinkling water on the unpaved internal roads on a regular

Others:-

- All mandatory approvals and permission as required from Director of Explosives, Fire Department etc. should be obtained.
- and Fire Detection and Suppression System etc. must be ensured Provision of Effective Controls and Building Management Systems such as Automatic Fire

Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal. dag no. 139,140,143,144,534, Mouza – Teghorial & Atghara JL No. 9 & 10, PS – Rajarhat, Rajarhat-Gopalpur Conditions for environmental clearance for the Residential Complex by M/s, Arch Infra Properties Pvt. Ltd. at RS

- Efficient management of indoor air quality must be ensured for health and safety of the users
- 7 Adequate measures to be adopted for water conservation during construction and operation stage should be considered of efficient irrigation equipment, evaporative cooling unit in air-conditioning system etc
- v. Rest room facilities should be provided for service population
- vi. Adequate access to fire tenders should be provided.

II. Operation Phase

Water supply:-

- per the West Bengal Ground Water Resources (Management, Control and Regulation) Act, 2005 Supply Ground water should not be abstracted without permission of the competent authority Water requirement during operation phase shall be met from Rajarhat-Gopalpur Municipality
- Use of water meter conforming to ISO standards should be installed at the inlet point of water uptake to monitor the daily water consumption and records to be maintained. Use of water efficient devices / fixtures and appliances should be promoted.
- Dual plumbing system to be installed for maximum use of treated wastewater
- The proponent must practice rainwater harvesting on regular basis

Sewage Treatment Plant:-

- rest will be discharged to municipal sewer line. As per the proposal submitted by the proponent, waste water shall be treated in STP. Treated waste water shall be partly reused for flushing, landscaping; internal road and pavement cleaning etc. and
- Water meter to be installed at STP inlet & discharge outlet point of treated water and regular records to be maintained
- iii. Provision of back up power for operation of STP to be provided

Emission from Diesel Generator Set:

- Noise barriers will be provided at appropriate locations so as to ensure that the noise levels do not enclosure at the manufacturing stage itself as per CPCB norms. exceed the prescribed standards. Diesel generator sets should be provided with integral acoustic
- The stack height and emissions from D.G. sets should conform to the norms of Central Pollution Control Board. The certification of space design for DG sets should be done by competent

Ensure Energy Efficiency:-

- incorporated. The desired level of R and U factors must be achieved. U factor for the top roof should not exceed 0.4 Watt/sq.m/degree centigrade with appropriate modifications of specifications and building technologies. The provisions of National Building Code 2005 should be strictly followed Use of energy efficient construction materials to achieve the desired thermal comfort should be
- Use of energy efficient electrical systems should be promoted. High efficiency lamps with electronic ballasts should be used.
- Energy efficient Motors and properly rated Transformers should be installed. Manufacturer's certificate to this effect shall be obtained and kept on record. Back up power supply should be
- Ξ. of the total power usage. Record of transmission losses shall be maintained. The proponent shall The power cabling shall be adequately sized as to maintain the distribution losses not to exceed 1% install permanent electrical metering to record demand (kVA), energy (kWh) and total power
- The project proponent should use solar energy at least for street lighting

Page

Municipality Ward No. 9, Dist - 24 Parganas (North), Wast Bengal. dag no. 139,140,143,144,534, Mouza – Teghorid & Alghard JL, No. 9 Conditions for environmental clearance & O. PS - Rajarhat, Rajarhat-Gopalpur Mis. Arch Infra Properties Pvt. Ltd. at RS

At least 30 KW of solar power to be generated and utilized in addition to stand alone solar street

Transport Management:

- transportation should be promoted. A dequate parking space Use of public mode of transportation should be promoted. Use of the least polluting type should be provided as per norms 0
- telecommunication lines should be provided. Pathways should be covered or shadowed by tree eanopy as far as practicable. Transport system should be such that traffic will be calm in neighbourhoods. Traffic within the project site should be restricted by regulation. Adequate vertical and horizontal elegrances of overhead electric power and

Solid Waste Management:-

- disposed off in consultation with concerned authority. 14 13 storage and segregation of biodegradable and non-biodegradable wastes. The solid waste is to be 2000. The proponent must develop the Solid Waste Management and Disposal Scheme ensuring The proponent should abide by the Municipal Solid Wastes (Management and Handling) Rules.
- installation of on-site compost plant should be provided and operation of the compost plant considering full occupancy of the apartments i.e the capacity of garbage disposal unit should be selected accordingly. Municipal Solid Waste and will be incorporated in the building layout plan. The proponent must install on-site compost plant for treatment of biodegradable fraction of Sufficient space for
- Ξ: The handling agency should also take care of the recyclable wastes like plastic, paper board, glass wastes from the housing complex. etc. and also inert materials in case the respective municipal authorities want to avoid any kind of
- used as fertilizer and soil supplement and The proponent should have sufficient area for horticulture where the compost generated can be also have arrangement for sale of excess quantity of
- Provision for treatment of leachate generation and odour control in on-site compost plant should be
- <u>۲</u>. of recyclables. segregation will be done at transfer stations to collect recyclables such as plastic, polythene, glass, metals, textiles, rubbers, leathers, paper etc. Separate compartments shall be provided for each type different collection and storage bins should be finally collected at transfer stations. Further The proponent should provide different coloured bins for different categories of waste and ensure segregation of biodegradable and non-biodegradable wastes. The solid waste
- Movement) Rules, 2008. Collection and storage of hazardous wastes during Pre-construction and Post-construction activity should be planned properly. The expected hazardous wastes should be disposed off separately as per the Hazardous, Wastes (Management, Handling and Transboundary) The proponent should abide by the Hazardous Wastes (Management, Handling and Transboundary
- viii. Spent oil from DG Sets should be stored in HDPE drums in isolated covered facility and disposed 2008. Spent oil from DG Sets should be disposed off through registered recyclers only off as per the Hazardous Wastes (Management, Handling and Transboundary Movement) Rules.

Others:

- Regular monitoring should be carried out during construction and operation phases. The implementation of Environmental Mahagement Plan should be carried out, as proposed.
- Ξ: The project proponent should provide guidelines to the project proponent should be provided to the project proponent should be provided to the project proponent should be provided guidelines to the project proponent should be provided to the project proponent should be provided to the project proponent should be provided to the project project proponent should be provided to the project proje ensure environmental protection. In-house environmental awareness campaigns should be carried out at regular intervals to

dag no. 139,140,143,144,534, Mouza — Teghoria & Atghara, JL No. 9 & 10, PS — Rajarhat, Rajarhat-Gopalpur Municipality Ward No. 9, Dist — 24 Parganas (North). Wast Bengal Conditions for environmental clearance for the Residential Complex by Ms. Arch Infra Properties Pvt. Ltd. at RS

- the National Building Code 2005. Fire fighting systems should be designed in compliance with the WBFS and NBC norms Preventive measures should be adopted for Risk & Disaster Management as per the provisions of
- 7 Corporate Social Responsibility programmes. The Corporate Social Responsibility Plan with specific financial commitment should be implemented for the proposed project. At least 2% of the total project cost should be utilized for Corporate Social Responsibility programmes.
- Government of West Bengal, vide No. EN/3170/11-1V-7/001/2009 dated 10.12.2009 proponent should abide by the Direction issued by the Department of Environment
- ≤. Environmental Management Information System shall be maintained properly.
- The proponent should restrict the use of glazed surface as per National Building Code, 2005

Part-B GENERAL CONDITIONS

- The environmental clearance accorded shall be valid for a period of 7 years æ. for the proposed
- competent authorities. Prior Consent-to-Establish (NOC) for the proposed project must be obtained from WBPCB by the All other statutory clearances should be obtained by project proponent from the
- Ξ. Ħ salient features of the proposed project. The proponent should maintain a display board at the site, providing detailed information on the
- and spirit, The environmental safeguards contained in the EIA/EMP report should be implemented in letter
- < ownership, maintenance of management of the project to any other entity the successor management of the project in the event of the project proponent transferring the All the conditions, liabilities and legal provisions contained in the EC shall be equally applicable to
- Zi. construction phase. All the labourers to be engaged for construction works should be screened for health and adequately treated before issue of work permits. Provision should be made for the supply of kerosene or cooking gas to the labourers during
- ≦: implementation of the suggested safeguard measures. project proponent should make financial provision in the total budget of the project for
- complete set of all the documents should also be forwarded to the State Level Environment Impact cooperation, facilities and documents / data by the project proponents during their inspection. A Six monthly monitoring reports should be submitted to the West Bengal Pollution Control Board, Assessment Authority, West Bengal. who would be monitoring the implementation of environmental safeguards and should be given full
- Σ the project, the project would require a fresh appraisal by the SEIAA, West Bengal. The Environment (Protection) Act, 1986, will be applicable. In case of any change(s) in the scope of In case of any violation of the conditions laid down in this Environmental Clearance, Section 16 of
- \times satisfactory manner. 1986, to ensume effective implementation of the suggested safeguard measures in a time-bound and additional safeguard measures subsequently, if found necessary, and to take action including revoking of the environmental (Protection) Act, Level Environment Impact Assessment Authority, West Bengal reserves the right to add
- Σ. region of which one shall be in the vernacular language of the locality concerned date of issue of the clearance letter, at least in two local newspapers that are widely circulated in the with the State Equilition Control Board / Committee and may also be seen at website of the SEIAA, environmental clearance by the SEIAA, West Bengal and copies of the clearance letter are available West Bengal (http://environmentwb.gov.in). This should be advertised within seven days from the Proponent should inform the public that the proposed project has been accorded

Municipality Ward No. 9, Dist - 24 Parganas (North), West Bengal dag no. 139,140,143,144,534, Mouza — Teghoria, & Atgliana Conditions for environmental clearance for the K JENO. 9 & 10 PS – Rajarhat, Rajarhat-Gopalpur plex by M/s. Arch Infra Properties Pvt. Ltd. at RS

- ž: All other statutory clearances such as the approvals for storage of diesel from Chief Controller of Explosives, Civil Aviation Department (if required) etc. shall be obtained by project proponents from the competent authorities,
- the project, should be made in explicit and transparent manner. sustained Operation and Maintenance (O&M) of the common facilities (STP, Rainwater harvesting system, Solid waste management system, Solar street lights etc.) even after transfer of ownership of Provision for incorporation of appropriate conditions in the Sale Agreement / Deed, for ensuring
- Χ<u>:</u> Impact Assessment Notification 2006 and their amendments Environment (Protection) Act, 1986, the Hazardous Wastes (Management, Handling and Transboundary Movement) Rules, 2008, the Public Liability Insurance Act, 1991, the Environment Control of Pollution) Act, 1974, the Air (Prevention and Control of Pollution) Act, 1981, Environment (Protection) Act, 1986, the Hazardous Wastes (Management, Handling The above stipulations would be enforced along with those under the Water (Prevention and the
- The contact details of the proponent and the name of the consultant are given below

Name of the Consultant	l elephone Number, Fax Number	Email		Address	Name of the Contact person with
Mr. Partho Pratim Dutta	Ph no. 3322275411, Fax no-913322275410	info@archgroup.co.in	Koj-70016	199A, Park Street, Siddha Park, room no5B, 5th floor,	1 1



(Sandipan Mukherjee, IFS) Chief Environment Officer & Member Secretary, SEIAA

Date: 05/07/2016

No. 1471 / EN/T-II-1/074/2014 /1(3)

Copy forwarded to :-

- 1. Secretary, SEAC & M.S. WBPCB
- Government of India, A-3, Chandrashekharpur, Bhubaneswar Officer-in-Charge, Regional Office (Eastern Zone), Ministry of Environment & Forests, 751 023, Orissa
- 3. Guard file / Record file.

Sd/-

Chief Environment Officer & Member Secretary, SEIAA

Conditions for environmental clearance for the Residebilal Complex by M/s. Arch Infra Properties Pvt. Ltd. at RS dag no. 139,140,143,144,534, Mouza – Teghoria & Algeria, JL No. 9 & 10, PS – Rajarhat, Rajarhat-Gopalpur Municipality Ward No. 9, Dist – 24 Parganas (North), West Bengal

LIST OF TREES PROPOSED FOR PLANTATION

Annexure – I

<u>.</u>	
BOTANICAL NAME	
n en	
149. N.C.	
COMMON NAME	100 mm f
QUANTITY	

	15.	F7	10.	9.	8.	7.	6,	5.	4.	μ	2.	ij	SI. No.
	Artocarpus heterophyllus	Bauhinia variegata	Lagerstroemia speciosa	Alstonia scholaris	Jacaranda mimosifolia	Cassia fistula	Azadirachta indica	Mimusops elengi	Ficus elastica	Delonix regia	Michelia champaca	Polyalthia longifolia	BOTANICAL NAME
	IS								-			- 17 mg	
Total	Kanthal	Raktakanchan	Jarul	Chhatim,	Jacaranda	Bandarlathi	Neem	Bakul	Rubber	Gulmohor	Champa	Debdaru	COMMON NAME
280	10	25	25	25	25	25	20	50	10	25	20	20	QUANTITY

List of Existing Trees to be retained

		4.	က	2.	'n	SI. No.
-		Azadirachta indica	Syzygium cumini	Mangifera indica	Cocos nucifera	SI. No. BOTANICAL NAME
		Weem	Jamun	Aam	Narikel	соммои наме
	06	01	01	03	01	QUANTITY